

TUCHEM VITON®



Suction and delivery hose designed according to EN 12115 standards for hot oils, chemical and petro-chemical products.

DESCRIPTION

Tube

Viton®, black

Reinforcement

synthetic plies, a/s copper wire to discharge static electricity, galvanized wire helices

Cover

smooth, CR, black, conductive, abrasion, ageing, ozone and oil resistant, cloth finish

Marking

green/white tape TUDERTECHNICA TUCHEM VITON®



embossed according to norm EN 12115

TUDERTECHNICA FKM EN12115:2011 DN SD PN 16 BAR Ω Q/Y

TECHNICAL CHARACTERISTICS

Temperature range

-25°C / +120°C (-13°F / +248°F)The operating temperature of the hose is directly dependent upon the specific fluid been conveyed and the length of time the fluid is in contact with the hose

Vacuum

675 mmHg (26,6 inHg)

Electrical properties

type Ω according to norm EN 12115 (R<10⁶ Ω)

Norm

EN12115

TRbF 131/2

Inside diameter		Outside diameter		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[mm]	[in]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
19	0,75	31	1,22	16	250	64	1000	0,81	0,54	125	4,92
25	1,00	37	1,46	16	250	64	1000	1,01	0,68	150	5,91
32	1,25	44	1,73	16	250	64	1000	1,19	0,80	175	6,89
38	1,50	51	2,00	16	250	64	1000	1,48	0,99	225	8,86
50	1,97	66	2,60	16	250	64	1000	2,30	1,54	275	10,83
51	2,00	67	2,64	16	250	64	1000	2,33	1,56	275	10,83
63,5	2,50	79,5	3,13	16	250	64	1000	3,32	2,22	350	13,78
75	2,95	91	3,58	16	250	64	1000	3,83	2,57	400	15,75
76	3,00	92	3,62	16	250	64	1000	3,87	2,59	400	15,75
100	3,94	116	4,57	16	250	64	1000	5,01	3,36	550	21,65
102	4,00	118	4,65	16	250	64	1000	5,05	3,38	550	21,65

Data refer to ambient temperature (20°C).