

GLIDETECH® VINEYARD HD



Extra flexible suction and delivery hose suitable for wine and vinification by-products with an improved resistance to higher pressure. Phthalates free tube, tested in compliance with REACH regulation.

DESCRIPTION

Tube

NR, white, phthalates free, tested in compliance with REACH regulation, meets FDA 21 CFR 177.2600, BFR RECOMMENDATION XXI CAT 2, DM 21.03.73 E SEGUENTI AND JAPAN-MINISTRY OF HEALTH AND WELFARE NOTICE NO.370,1959 AND NO.201, 2006. RAL REGISTRATION G-72

Reinforcement

Cover

synthetic plies, galvanized wire helices
wide corrugated, red, low friction material, non marking when dragged on the floor, abrasion, ageing, ozone, oil and chemical resistant, easy to clean

Sterilization

Marking

according to 3A Sanitary Standard Class II
TUDERTECHNICA GLIDETECH® VINEYARD HD

TUDERTECHNICA

GLIDETECH VINEYARD HD

TECHNICAL CHARACTERISTICS

Temperature range

-40°C / +80°C (-40°F / +176°F)

Vacuum

675 mmHg (26,6 inHg)

Norm

ISO 1307 for dimensional tolerances
3A Sanitary Standard Class II

Inside diameter		Outside diameter		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[mm]	[in]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
25	1,00	-	-	16	250	60	900	0,91	0,61	105	4,13
38	1,50	-	-	16	250	60	900	1,41	0,94	120	4,72
51	2,00	-	-	16	250	60	900	2,24	1,50	150	5,91
63,5	2,50	-	-	16	250	60	900	2,82	1,89	195	7,68
76	3,00	-	-	16	250	60	900	3,55	2,38	225	8,86
102	4,00	-	-	16	250	60	900	4,44	2,97	375	14,76

Other diameters, wall thickness, cover colours and pressure only on specific request.
Data refer to ambient temperature (20°C).